



APPLICATION:

Designed for rental applications, where quick installation and light-weight performance are essential. HIVE ODX Series delivers high resolution, high contrast images in a rigid yet light-weight diecast aluminum form factor. All cabinets in ODX series are 500mm x 1000mm. Assembly is achieved through a precision tensionable bayonet system and allows panels to be removed from the center of an existing screen for easy maintenance.

TECHNICAL SPECIFICATIONS

- Pixel Pitch: 3.91 mm
- Drive Method: 1/16
- LED Type: SMD2020
- Brightness: > 5500 nit
- Pixel Density: 65,536 pix/m²
- Viewing Angle: 140°H and 140°v
- Module Size: 250w x 250h mm (9.84 x 9.84 in)
- Cabinet Size: 500w 1000h (19.68 x 19.68 x 3.46 in)
- Cabinet Weight: 6kg/24kg m² (13.2 lbs. 52.8 m²)
- Cabinet Material: Diecast Aluminium
- Average/Max Power Consumption: 200W/600W m²
- Refresh Rate: 3840HZ
- Voltage : 100-240V
- IP Rating: IP65 front side / IP54 back side
- Operating Temperature : -20 - 50°C (10 - 90% RH)
- Life Span (hrs): ≥ 50,000
- Compliance Standard: CE, RoHS, CCC
- Typical Control System is NovaSTAR



FOR MORE INFORMATION:
HIVELED.COM